

Laminate Surface | Agrifiber Core Doors | 20-min & Non-Rated
Neutral Pressure, Positive Pressure, Environmental

Standard Models: AAGFiber

Environmental Models: AAGFiber-NAUF, AAGFiber-FSC, AAGFiber-NAUF FSC

Product Features and Specifications Interior use only
Thickness 1-3/4"

Maximum Size 4/0 x 9/0

Minimum Size 1-5 1/2" x 5-11'

Surface Material High Pressure Decorative Laminate

Fire-Rating

	ITS-WH - Max 20 minute *Approved sizes may vary based on fire listing			
	Non Rated	NP	Cat. A (PP)	Cat. B (PPFM)
Single	4/0x9/0	4/0x9/0	4/0x9/0	4/0x9/0
Pair	8/0x8/0	8/0x8/0	8/0x8/0	8/0x8/0
DE Pair	8/0x8/0	8/0x8/0	8/0x8/0	8/0x8/0

Construction Bonded

Crossbands One Piece High Density Fiberboard (HDF)

Vertical Edges* SCL with Laminate edge band
Additional stile options available upon request

Horizontal Edges* Wood

Face & Core Assembly Adhesive Type 1

Core LD1 AgriFiber (complies with ANSI A208.1). See WDMA Performance Level below.

Lite Openings Wood or metal lite kits available

Louvers

- Wood
- Metal

Warranty Lifetime. No exterior warranty

Finished Accessories

- Vertical Edges
- Lite Mouldings
- Louvers

 *painted or stained upon request

Security Ratings Class 40, highest security rating possible per UBC standard 41-1 & ASTM F-476 section 18

Environmental Options & LEED Credit Contribution
 (Not all credits may be available with some constructions)

- MR 4-Recycled Content- all models
- MR 6- Rapidly Renewable Materials - all models
- MR 7-Certified Wood-upon request
- IEQ 4.4-Low-Emitting Materials- all NAUF models
No Added Urea Formaldehyde Resins
- CARB Phase II Compliant

Quality Standards (Quality Assurance/ Industry Standards)

Aesthetic: WDMA I.S.1A Architectural Wood Flush Doors (Standard construction)
 *Other association aesthetic standards upon request
 WDMA Performance Duty Level: Heavy Duty
 *Product does not require blocking for surface hardware

Note: Mohawk Flush Doors® are manufactured per the standards listed on this page.

Specifications are subject to change without notice.

*Note: Fire-Rated doors will be constructed per label service listing and may deviate from above.