

**Laminate Surface | Radiation-Shielded Core Doors | 20 min & Non-Rated**
*Neutral Pressure, Positive Pressure, Environmental*

Standard Models: LEAD APC LEAD ASCL

Environmental Models: LEAD APC NAUF LEAD ASCL NAUF

| Product Features and Specifications  | Particleboard Core   | Structural Composite Lumber  |
|--|--|--|
| <b>Thickness</b>   | 1-3/4"   | Same   |
| <b>Lead Thickness</b>  | 1/32", 1/16", 1/8" (Contact sales for other thickness)   | Same   |
| <b>Lead Location</b>   | One sheet, narrow side. (Review hardware applications when ordering)   | Same   |
| <b>Fire Rating</b>   | 20 minute  | Same   |
| <b>Maximum Size</b>  | ITS-WH: Single: 4/0x8/0 Standard Pairs: 8/0x8/0  | Same   |
| <b>Minimum Size</b>  | 0-11 3/8 x 4-0   | Same   |
| <b>Astragal at Pairs</b>   | Lead-lined Metal Edge & Astragal   | Same   |
| <b>Surface Materials</b>   | High Pressure Decorative Laminate  | Same   |
| <b>Crossbands</b>  | Engineered Composite   | Same   |
| <b>Vertical Edges</b>  | Manufacturer's standard construction per label service listing   | Same   |
| <b>Horizontal Edges</b>  | Manufacturer's standard construction per label service listing   | No Horizontal Rails Required   |
| <b>Face &amp; Core Assembly Adhesive</b>   | Type 1   |  |
| <b>Core</b>  | Particleboard core (which complies with ANSI A208.1).  | Structural Composite Lumber  |
| <b>Lite Openings</b>   | Refer to Appendix N  | Same   |
| <b>Finished Accessories</b>  | <ul style="list-style-type: none"> <li>•Vertical Edges</li> <li>•Lite Mouldings</li> <li>•Louvers: available as stained or painted upon request</li> </ul>   | Same   |
| <b>Warranty</b>  | Full; life of original installation. No exterior warranty  | Same   |
| <b>Door Weight</b>   | 1/32" lead = 7.7 lbs per sq ft.<br>1/16" lead = 9.2 lbs per sq ft.<br>1/8" lead = 13 lbs per sq ft.  | 1/32" lead = 9.1 lbs per sq ft.<br>1/16" lead = 11.1 lbs per sq ft.<br>1/8" lead = 15.1 lbs per sq ft. |
| <b>Environmental Options &amp; LEED Credit Contribution (Not all credits may be available with some constructions)</b> | <ul style="list-style-type: none"> <li>•Certified Wood - contact sales</li> <li>•Low-Emitting Materials- all UF models</li> <li>No Added Urea Formaldehyde Resins</li> <li>•CARB Phase II Compliant</li> </ul> | Same   |
| <b>Quality Standards (Quality Assurance/ Industry Standards)</b>   | Aesthetic: WDMA I.S.1A Architectural Wood Flush Doors (Standard construction)<br>*Other association aesthetic standards upon request   |  |

Note: Mohawk Flush Doors® are manufactured per the standards listed on this page.

Specifications are subject to change without notice.

\*Note: Fire-Rated doors will be constructed per label service listing and may deviate from above.