

Paintable Surface | Fire-Resistant Composite Core Doors | 45-90 min
Neutral Pressure, Positive Pressure, Environmental

Standard Models: AMINERAL, APC-45

Environmental Models: AMINERAL_FSC, AMINERAL_NAUF FSC, AMINERAL_NAUF, APC-45 NAUF, APC-45 FSC, APC-45 NAUF FSC

Product Features and Specifications Interior use only
Thickness 1-3/4"

Maximum Size

	ITS-WH and UL		
	NP	Cat. A (PP)	Cat. B (PPFM)
Single	4/0x10/0	4/0x10/0	4/0x10/0
Pair	8/0x8/0	8/0x9/0	8/0x9/0
DE Pair	8/0x8/0 (45 min only)	8/0x8/0	8/0x8/0

Minimum Size 0/8x1/10 or 1/10x0/8

Surface Material

- Birch
- MDO (Medium Density Overlay)

Crossbands One Piece High Density Fiberboard (HDF)

Vertical Edges* Manufacturer's standard construction per label service listing with edge band to match face.

Horizontal Edges* Manufacturer's standard construction per label service listing.

Face & Core Assembly Adhesive Type 1

Core Fire-resistant composite per label service listing.

Lite Openings Veneer clad or metal lite kits available

Louvers Fusible link metal

Warranty Lifetime. No exterior warranty

Factory Finish

- Prime
- Opaque

Security Ratings

Mineral Core- class 30 per UBC standard 41-1 and ASTM F-476 Section 18
 Particleboard Core- Class 40 per UBC standard 41-1 and ASTM F - 476 Section 18

Environmental Options & LEED Credit Contribution (Not all credits may be available with some constructions)

- MR 4-Recycled Content- all models
- MR 7-Certified Wood-upon request
- IEQ 4.4-Low-Emitting Materials- all NAUF models
No Added Urea Formaldehyde Resins
- CARB Phase II Compliant

Quality Standards (Quality Assurance/ Industry Standards)

Aesthetic: WDMA I.S.1A Architectural Wood Flush Doors (Standard construction)
 *Other association aesthetic standards upon request
 WDMA Performance Duty Level:
 *Particle Core: Extra Heavy Duty
 *Mineral Core without Blocking - Below Standard
 *Mineral Core with Blocking - Extra Heavy Duty
 (Blocking for mineral core doors provided upon request)

Note: Mohawk Flush Doors® are manufactured per the standards listed on this page.

Specifications are subject to change without notice.

*Note: Fire-Rated doors will be constructed per label service listing and may deviate from above.