

**Paintable Surface | Radiation-Shielded Core Doors | 20 min**

*Neutral Pressure, Positive Pressure, Environmental*

Standard Models: LEAD APC LEAD ASCL  
 Environmental Models: LEAD APC NAUF LEAD ASCL NAUF

Product Features & Specifications	Particleboard Core	Structural Composite Lumber Core
<b>Thickness</b>	1-3/4"	Same
<b>Lead Thickness</b>	1/32", 1/16", 1/8" (Contact sales for other thickness)	Same
<b>Lead Location</b>	One sheet, narrow side. (Review hardware applications when ordering)	Same
<b>Fire Rating</b>	20 minute	Same
<b>Maximum Size</b>	ITS-WH: Single: 4/0x8/0 Standard Pairs: 8/0x8/0	Same
<b>Minimum Size</b>	0-11 3/8 x 4/0	Same
<b>Astragal at Pairs</b>	Lead-lined Metal Edge & Astragal	Same
<b>Surface Materials</b>	•Birch •MDO (Medium Density Overlay)	Same
<b>Crossbands</b>	Engineered Composite	Same
<b>Vertical Edges</b>	Manufacturer's standard construction per label service listing	Same
<b>Horizontal Edges</b>	Manufacturer's standard construction per label service listing	No horizontal rails required
<b>Face &amp; Core Assembly Adhesive</b>	Type 1	Same
<b>Core</b>	Wood based Particleboard core (complies with ANSI A208.1).	Structural Composite Lumber
<b>Lite Openings</b>	Refer to Appendix N	Refer to Appendix N
<b>Warranty</b>	Full, life of original installation. No exterior warranty.	Same
<b>Factory Finish</b>	•Prime •Opaque: Available on MDO only.	Same
<b>Door Weight</b>	1/32" lead = 7.7 lbs per sq ft. 1/16" lead = 9.2 lbs per sq ft. 1/8" lead = 13 lbs per sq ft.	1/32" lead = 9.1 lbs per sq ft. 1/16" lead = 11.1 lbs per sq ft. 1/8" lead = 15.1 lbs per sq ft.
<b>Environmental Options &amp; LEED Credit Contribution (Not all credits may be available with some constructions)</b>	•Certified Wood-upon request •Low-Emitting Materials- all NAUF models No Added Urea Formaldehyde Resins •CARB Phase II Compliant	Same
<b>Quality Standards (Quality Assurance/ Industry Standards)</b>	Aesthetic: WDMA I.S.1A Architectural Wood Flush Doors (Standard construction)	Same

Note: Mohawk Flush Doors® are manufactured per the standards listed on this page.  
 Specifications are subject to change without notice.  
 \*Note: Fire-Rated doors will be constructed per label service listing and may deviate from above.