

Paintable Surface | Radiation-Shielded Core Doors | 45-60 min
Neutral Pressure, Positive Pressure, Environmental

Standard Models: LEAD MINERAL
 Environmental Models: LEAD MINERAL NAUF

Product Features and Specifications Mineral Core
Thickness 1-3/4"

Lead Thickness 1/32", 1/16", 1/8"

Lead Location One sheet, narrow side. (Review hardware applications when ordering)

Label Agency ITS-WH

Fire Rating 45-60 minute

Maximum Size ITS-WH: Single: 4/0x8/0 Standard Pairs: 8/0x8/0

Minimum Size 1-7 1/2 x 4/0

Astragal at Pairs Lead Lined Metal Edge & Astragal

Surface Materials •Birch •MDO (Medium Density Overlay)

Crossbands One Piece High Density Fiberboard (HDF)

Vertical Edges Manufacturer's standard construction per label service listing

Horizontal Edges Manufacturer's standard construction per label service listing

Face & Core Assembly Adhesive Type 1

Core Fire-Resistant Composite per label service listing

Lite Openings Refer to Appendix N

Finished Accessories •Vertical Edges •Lite Mouldings

Factory Finish •Prime
 •Opaque - Available on MDO only.

Warranty Full; life of original installation. No exterior warranty

Door Weight 1/32" lead = 5.8 lbs per sq ft.
 1/16" lead = 7.8 lbs per sq ft.
 1/8" lead = 13.8 lbs per sq ft.

Environmental Options & LEED Credit Contribution
 (Not all credits may be available with some constructions)

- Certified Wood - contact sales
- Low-Emitting Materials- all UF models
- No Added Urea Formaldehyde Resins
- CARB Phase II Compliant

Quality Standards (Quality Assurance/ Industry Standards)

Aesthetic: WDMA I.S.1A Architectural Wood Flush Doors (Standard construction)
 *Other association aesthetic standards upon request

Note: Mohawk Flush Doors® are manufactured per the standards listed on this page.
 Specifications are subject to change without notice.
 *Note: Fire-Rated doors will be constructed per label service listing and may deviate from above.

