

Paintable Surface | Staved Lumber Core Doors | 20-min & Non-Rated

Neutral Pressure, Positive Pressure, Environmental

Standard Models: ASLC

Environmental Models: ASLC-NAUF, ASLC-FSC, ASLC-NAUF FSC

Product Features and Specifications Interior use only

Thickness 1-3/4", 2", 2-1/4"

Maximum Size 4/0 x 8/0 Singles 8/0 x 8/0 Pairs (1-3/8" & 1-3/4" doors)
4/0 x 9/0 Singles 8/0 x 9/0 Pairs (2" & 2-1/4" doors)

Minimum Size 1-6" x 5-11'

Surface Material •Birch
•MDO (Medium Density Overlay)

Fire-Rating

	ITS-WH and UL- Max 20 minute			
	Non Rated	NP	Cat. A (PP)	Cat. B (PPFM)
Single	4/0x10/0	4/0x10/0	4/0x10/0	4/0x10/0
Pair	8/0x10/0	8/0x10/0	8/0x9/0	8/0x9/0
DE Pair	8/0x10/0	8/0x10/0	8/0x9/0	8/0x9/0
1-3/8" Single	4/0x10/0	3/0x7/0	NA	3/0x7/0

Construction Bonded

Crossbands One Piece High Density Fiberboard (HDF)

Vertical Edges* SCL with Veneer edge band
Additional stile options available upon request

Horizontal Edges* Wood

Face & Core Assembly Adhesive Type 1

Core Staved Lumber. See WDMA Performance Level below.

Lite Openings Wood or metal lite kits available

Louvers •Wood
•Metal

Warranty Lifetime. No exterior warranty

Factory Finish •Prime
•Opaque

Security Ratings Class 40, highest security rating possible per UBC standard 41-1 & ASTM F-476 section 18

Environmental Options & LEED Credit Contribution
(Not all credits may be available with some constructions)

- MR 4-Recycled Content- all models
- MR 7-Certified Wood-upon request
- IEQ 4.4-Low-Emitting Materials- all NAUF models
No Added Urea Formaldehyde Resins
- CARB Phase II Compliant

Quality Standards (Quality Assurance/ Industry Standards) Aesthetic: WDMA I.S.1A Architectural Wood Flush Doors (Standard construction)
*Other association aesthetic standards upon request
WDMA Performance Duty Level: Heavy Duty
*Product does not require blocking for surface hardware

Note: Mohawk Flush Doors® are manufactured per the standards listed on this page.

Specifications are subject to change without notice.

*Note: Fire-Rated doors will be constructed per label service listing and may deviate from above.