

**Veneer Surface | Fire-Resistant Composite Core Doors | 45-90 min**

*Neutral Pressure, Positive Pressure, Environmental*

Standard Models: AMINERAL, APC-45  
 Environmental Models: AMINERAL\_NAUF

**Product Features and Specifications Interior use only**

**Thickness** 1-3/4"

**Maximum Size**

	ITS-WH and UL		
	NP	Cat. A (PP)	Cat. B (PPFM)
Single	4/0x10/0	4/0x10/0	4/0x10/0
Pair	8/0x8/0	8/0x9/0	8/0x9/0
DE Pair	8/0x8/0 (45 min only)	8/0x8/0	8/0x8/0

**Minimum Size** 0/8x1/10 or 1/10x0/8

**Surface Material** Wood Veneers

**Crossbands** One Piece High Density Fiberboard (HDF)

**Vertical Edges** Manufacturer's standard construction per label service listing with edge band to match face.

**Horizontal Edges** Manufacturer's standard construction per label service listing.

**Face & Core Assembly Adhesive** Type 1

**Core** Fire-resistant composite per label service listing.

**Lite Openings** Veneer clad or metal lite kits available

**Louvers** Fusible link metal

**Warranty** Lifetime. No exterior warranty

**Factory Finish** •Clear, Standard Stain, Custom Color. Meets WDMA TR-8 and AWS System 9.

**Security Ratings** Mineral Core- class 30 per UBC standard 41-1 and ASTM F-476 Section 18  
 Particleboard Core- Class 40 per UBC standard 41-1 and ASTM F - 476 Section 18

**Acoustic Ratings** 21-30 - Operable with recommended seals. Must be specified.

**Environmental Options & LEED Credit Contribution (Not all credits may be available with some constructions)**

- Recycled Content- all models
- Rapidly Renewable Materials- all models with Bamboo veneer
- Certified Wood- contact factory.
- Low-Emitting Materials- all NAUF models  
 No Added Urea Formaldehyde Resins
- CARB Phase II Compliant

**Quality Standards (Quality Assurance/ Industry Standards)**

Aesthetic: WDMA I.S.1A Architectural Wood Flush Doors (Standard construction)  
 \*Other association aesthetic standards upon request  
 WDMA Performance Duty Level  
 \*Particleboard Core: Extra Heavy Duty  
 \*Mineral Core without Blocking - Below Standard  
 \*Mineral Core with Blocking - Extra Heavy Duty  
 (Blocking for mineral core doors provided upon request)

Note: Mohawk doors are manufactured per the standards listed on this page.  
 Specifications are subject to change without notice.  
 \*Note: Fire-Rated doors will be constructed per label service listing and may deviate from above.