

**Veneer Surface | Radiation-Shielded Core Doors | 20 min & Non-Rated**
*Neutral Pressure, Positive Pressure, Environmental*

Standard Models: LEAD APC LEAD ASCL

Environmental Models: LEAD APC NAUF LEAD ASCL NAUF

Product Features and Specifications	Particleboard Core	Structural Composite Lumber
<b>Thickness</b>	1-3/4"	Same
<b>Lead Thickness</b>	1/32", 1/16", 1/8" (Contact sales for other thickness)	Same
<b>Lead Location</b>	One sheet, narrow side. (Review hardware applications when ordering)	Same
<b>Fire Rating</b>	20 minute	Same
<b>Maximum Size</b>	ITS-WH: Single: 4/0x8/0 Standard Pairs: 8/0x8/0	Same
<b>Minimum Size</b>	0-11 3/8 x 4-0	Same
<b>Astragal at Pairs</b>	Lead-lined Metal Edge & Astragal	Same
<b>Surface Materials</b>	Wood Veneers	Same
<b>Crossbands</b>	Engineered Composite	Same
<b>Vertical Edges</b>	Manufacturer's standard construction per label service listing	Same
<b>Horizontal Edges</b>	Manufacturer's standard construction per label service listing	No Horizontal Rails Required
<b>Face &amp; Core Assembly Adhesive</b>	Type 1	
<b>Core</b>	Woodbased Particleboard Core (which complies with ANSI A208.1).	Structural Composite Lumber
<b>Lite Openings</b>	Refer to Appendix N	Same
<b>Factory Finish</b>	Clear, Standard Stain, Custom Color. Meets WDMA TR-8 and AWS System 9.	Same
<b>Warranty</b>	Full; life of original installation. No exterior warranty	Same
<b>Door Weight</b>	1/32" lead = 7.7 lbs per sq ft. 1/16" lead = 9.2 lbs per sq ft. 1/8" lead = 13 lbs per sq ft.	1/32" lead = 9.1 lbs per sq ft. 1/16" lead = 11.1 lbs per sq ft. 1/8" lead = 15.1 lbs per sq ft.
<b>Environmental Options &amp; LEED Credit Contribution (Not all credits may be available with some constructions)</b>	<ul style="list-style-type: none"> <li>•Rapidly Renewable Materials all models with Bamboo veneer</li> <li>•Certified Wood - contact sales</li> <li>•Low-Emitting Materials- all UF models</li> <li>No Added Urea Formaldehyde Resins</li> <li>•CARB Phase II Compliant</li> </ul>	Same
<b>Quality Standards (Quality Assurance/ Industry Standards)</b>	Aesthetic: WDMA I.S.1A Architectural Wood Flush Doors (Standard construction) *Other association aesthetic standards upon request	

Note: Mohawk Flush Doors® are manufactured per the standards listed on this page.

Specifications are subject to change without notice.

\*Note: Fire-Rated doors will be constructed per label service listing and may deviate from above.