

**Veneer Surfaces | Structural Composite Lumber Doors | 20 min & Non-Rated**
*Neutral Pressure, Positive Pressure, Environmental*

Standard Models: ASCL

Environmental Models: ASCL-NAUF, ASCL-FSC, ACL-NAUF FSC

**Product Features and Specifications Interior use only**
**Thickness** 1-3/4", 1-3/8"

**Maximum Size** 4/0 x 10/0 Singles 8/0 x 10/0 Pairs (1-3/8" & 1-3/4")  
4/0 x 9/0 (20 min max)

**Minimum Size** 1-6" x 5-11'

**Surface Material** Wood Veneers

**Fire-Rating**

	ITS-WH and UL- Max 20 minute			
	Non Rated	NP	Cat. A (PP)	Cat. B (PPFM)
Single	4/0x10/0	4/0x10/0	4/0x10/0	4/0x9/6
Pair	8/0x10/0	8/0x10/0	8/0x9/0	8/0x9/0
DE Pair	8/0x10/0	8/0x8/0	8/0x9/0	8/0x9/0
1-3/8" Single	4/0x10/0	3/0x7/0	NA	3/0x7/0

**Construction** Bonded

**Crossbands** One Piece High Density Fiberboard (HDF)

**Vertical Edges\*** SCL with Veneer edge band  
Additional stile options available upon request

**Horizontal Edges\*** Wood

**Face & Core Assembly Adhesive** Per requirements of WDMA I.S. 1A, C-6

**Core** Type 1

**Lite Openings** Wood or metal lite kits available

**Louvers**

- Wood
- Metal

**Warranty** Lifetime. No exterior warranty

**Factory Finish** •Clear, Standard Stain, Custom Color. Meets WDMA TR-8 and AWS System 9.

**Security Ratings** Class 40, highest security rating possible per UBC standard 41-1 & ASTM F-476 section 18

**Environmental Options & LEED Credit Contribution**  
 (Not all credits may be available with some constructions)
 

- MR 4-Recycled Content- all models
- MR 6-Rapidly Renewable Materials - Bamboo veneer
- MR 7-Certified Wood-upon request
- IEQ 4.4-Low-Emitting Materials- all NAUF models  
No Added Urea Formaldehyde Resins
- CARB Phase II Compliant

**Quality Standards (Quality Assurance/ Industry Standards)**

Aesthetic: WDMA I.S.1A Architectural Wood Flush Doors (Standard construction)  
 \*Other association aesthetic standards upon request  
 WDMA Performance Duty Level: Extra Heavy Duty  
 \*Product does not require blocking for surface hardware

Note: Mohawk Flush Doors® are manufactured per the standards listed on this page.

Specifications are subject to change without notice.

\*Note: Fire-Rated doors will be constructed per label service listing and may deviate from above.