

Veneer Surface | Staved Lumber Core Doors | 20-min & Non-Rated
Neutral Pressure, Positive Pressure, Environmental

Standard Models: ASLC

Environmental Models: ASLC-NAUF, ASLC-FSC, ASLC-NAUF FSC

Product Features and Specifications Interior use only
Thickness 1-3/4", 2", 2-1/4"

Maximum Size 4/0 x 8/0 Singles 8/0 x 8/0 Pairs (1-3/8" & 1-3/4" doors)
 4/0 x 9/0 Singles 8/0 x 9/0 Pairs (2" & 2-1/4" doors)

Minimum Size 1-6" x 5-11"

Surface Material Wood Veneers

Fire-Rating

	ITS-WH and UL- Max 20 minute			
	Non Rated	NP	Cat. A (PP)	Cat. B (PPFM)
Single	4/0x10/0	4/0x10/0	4/0x10/0	4/0x10/0
Pair	8/0x10/0	8/0x10/0	8/0x9/0	8/0x9/0
DE Pair	8/0x10/0	8/0x10/0	8/0x9/0	8/0x9/0
1-3/8" Single	4/0x10/0	3/0x7/0	NA	3/0x7/0

Construction Bonded

Crossbands One Piece High Density Fiberboard (HDF)

Vertical Edges* SCL with Veneer edge band
 Additional stile options available upon request

Horizontal Edges* Wood

Face & Core Assembly Adhesive Type 1

Core Staved Lumber. See WDMA Performance Level below.

Lite Openings Wood or metal lite kits available

Louvers

- Wood
- Metal
- Fusible Link

Warranty Lifetime. No exterior warranty

Factory Finish •Clear, Standard Stain, Custom Color. Meets WDMA TR-8 and AWS System 9.

Security Ratings Class 40, highest security rating possible per UBC standard 41-1 & ASTM F-476 section 18

Environmental Options & LEED Credit Contribution
 (Not all credits may be available with some constructions)

- MR 4-Recycled Content- all models
- MR 6-Renewable Materials - all models with Bamboo veneer
- MR 7-Certified Wood-upon request
- IEQ 4.4-Low-Emitting Materials- all NAUF models
 No Added Urea Formaldehyde Resins
- CARB Phase II Compliant

Quality Standards (Quality Assurance/ Industry Standards)

Aesthetic: WDMA I.S.1A Architectural Wood Flush Doors (Standard construction)
 *Other association aesthetic standards upon request
 WDMA Performance Duty Level: Heavy Duty
 *Product does not require blocking for surface hardware

Note: Mohawk Flush Doors® are manufactured per the standards listed on this page.

Specifications are subject to change without notice.

*Note: Fire-Rated doors will be constructed per label service listing and may deviate from above.