

Laminate Surface | Agrifiber Core Doors | 20 min & Non-Rated
Neutral Pressure, Positive Pressure, Environmental

Standard Models (Bonded): AG FIBER

Environmental Models: AG FIBER-NAUF, AG FIBER-FSC, AG FIBER-NAUF-FSC

Product Features and Specifications Interior use only
Thickness 1-3/4"

Maximum Size 4/0 X 9/0

Minimum Size 1-5 1/2" x 5-11'

Surface Material High Pressure Decorative Laminate

Fire Rating 20 Minute (Approvals vary by door construction)

Construction Bonded

Crossbands Engineered Composite

Vertical Edges Mill Option with laminate edge band applied after faces
(Additional stile options available upon request-Contact Sales)

Horizontal Edges Wood

Face & Core Assembly Adhesive Type 1

Core Agrifiber

Lite Openings

- Wood
- Metal Vision Frame

Louvers Non-rated Only:
Wood
Metal

Finishing-Wood Accessories •Clear, Stain, Paint (Upon Request)

Warranty Limited Lifetime. No exterior warranty

Environmental Options & LEED Credit Contribution
 (Not all credits may be available with some constructions)

- MR 4-Recycled Content- all models
- MR 6- Rapidly Renewable Materials - all models
- MR 7-Certified Wood-upon request (Contact Sales)
- IEQ 4.4-Low-Emitting Materials- all NAUF models
- No Added Urea Formaldehyde Resins
- CARB Phase II Compliant

Quality Standards (Quality Assurance/ Industry Standards) Aesthetic: WDMA I.S.1A Architectural Wood Flush Doors (Custom Grade Only)

Note: Mohawk Flush Doors® are manufactured per the standards listed on this page.

Specifications are subject to change without notice.

*Note: Fire-Rated doors will be constructed per label service listing and may deviate from above.