

Laminate Surface | Particleboard Core Doors | 20 min & Non-Rated
Neutral Pressure, Positive Pressure, Environmental

Standard Models (Non-Bonded): PCFPC

Standard Models (Bonded): PC

Environmental Models: PC-NAUF, PC-FSC, PC-NAUF-FSC

Product Features and Specifications Interior use only
Thickness 1-3/4", 1-3/8"

Maximum Size 4/0 X 10/0 (Limitations apply-based on door construction)

Minimum Size 1-5 1/2" x 5-11' (PC Models) & 0/8' x 1/10' (PCFPC Models)

Surface Material High Pressure Decorative Laminate

Fire Rating 20 Minute (Approvals vary by door construction)

Construction Bonded (Laminate edge band available upon request)

Crossbands Engineered Composite

Vertical Edges Fir (Additional stile options available upon request-Contact Sales)

Horizontal Edges Wood

Face & Core Assembly Adhesive Type 1

Core Wood based Particleboard (complies with ANSI A208.1)

Lite Openings

- Wood
- Metal Vision Frame

Louvers Non-rated Only:

- Wood
- Metal

Finishing-Wood Accessories

- Clear, Stain, Paint (Upon Request)

Warranty Limited Lifetime. No exterior warranty

Environmental Options & LEED Credit Contribution
 (Not all credits may be available with some constructions)

- MR 4-Recycled Content- all models
- MR 7-Certified Wood-upon request (Contact Sales)
- IEQ 4.4-Low-Emitting Materials- all NAUF models
- No Added Urea Formaldehyde Resins
- CARB Phase II Compliant

Quality Standards (Quality Assurance/ Industry Standards) Aesthetic: WDMA I.S.1A Architectural Wood Flush Doors (Custom Grade Only)

Note: Mohawk Doors® are manufactured per the standards listed on this page.

Specifications are subject to change without notice.

*Note: Fire-Rated doors will be constructed per label service listing and may deviate from above.