

Paintable Surface - Birch | Structural Composite Lumber Doors | 20 min & Non-Rated
Neutral Pressure, Positive Pressure, Environmental

Standard Models (Bonded): SCL

Environmental Models (Bonded): SCL-NAUF, SCL-FSC, SCL-NAUF FSC

Product Features and Specifications Interior use only
Thickness 1-3/8", 1-3/4"

Maximum Size 4/0 X 8/0

Minimum Size 1-5 1/2" x 5-11"

Surface Material Paint Grade Birch

Fire-Rating 20 Minute (Approvals vary by door construction)

Construction Bonded

Crossbands Engineered Composite

Vertical Edges* Mill Option-Fir/Aspen
(Additional stile options available upon request)

Horizontal Edges Wood

Face & Core Assembly Adhesive Type 1

Core Structural Composite Lumber (SCL).

Lite Openings

- Wood
- Metal Vision Frame

Louvers Non-rated Only:

- Wood
- Metal

Factory Finish

- Primed
- Standard Color
- Custom Color

Warranty Limited Lifetime. No exterior warranty.

Environmental Options & LEED Credit Contribution
 (Not all credits may be available with some constructions)

- MR 4-Recycled Content- all models
- MR 7-Certified Wood-upon request (Contact Sales)
- IEQ 4.4-Low-Emitting Materials- all NAUF models
- No Added Urea Formaldehyde Resins
- CARB Phase II Compliant

Quality Standards (Quality Assurance/ Industry Standards) Aesthetic: WDMA I.S.1A Architectural Wood Flush Doors (Custom Grade Only)

Note: Mohawk Flush Doors® are manufactured per the standards listed on this page.

Specifications are subject to change without notice.

*Note: Fire-Rated doors will be constructed per label service listing and may deviate from above.