

Rustic Embossed Hardboard | Particleboard Core Doors | 20 min & Non-Rated
Neutral Pressure, Positive Pressure, Environmental

Standard Models (Non-Bonded): PCFPC Standard Models (Bonded): PC
 Environmental Models: PC-NAUF, PC-FSC, PC-NAUF-FSC

Product Features and Specifications Interior use only

Thickness	1-3/4", 1-3/8"
Maximum Size	4/0 X 10/0 (Limitations apply-based on door construction)
Minimum Size	1-5 ½" x 5-11' (PC Models) & 0/8' x 1/10' (PCFPC Models)
Surface Material	Rustic Hardboard
Fire Rating	20 Minute (Approvals vary by door construction)
Construction	Loose Lay-up (Bonded construction upon request)
Crossbands	Engineered Composite
Vertical Edges	Fir (Additional stile options available upon request-Contact Sales)
Horizontal Edges	Wood
Face & Core Assembly Adhesive	Type 1
Core	Wood based Particleboard (complies with ANSI A208.1)
Lite Openings	•Wood •Metal Vision Frame
Louvers	Non-rated Only: Wood Metal
Factory Finish Options	•Primed •Standard Color •Custom Color
Warranty	Limited Limited. No exterior warranty
Environmental Options & LEED Credit Contribution (Not all credits may be available with some constructions)	•MR 4-Recycled Content- all models •MR 7-Certified Wood-upon request (Contact Sales) •IEQ 4.4-Low-Emitting Materials- all NAUF models No Added Urea Formaldehyde Resins •CARB Phase II Compliant
Quality Standards (Quality Assurance/ Industry Standards)	Aesthetic: WDMA I.S.1A Architectural Wood Flush Doors (Custom Grade Only)

Note: Mohawk Doors® are manufactured per the standards listed on this page.
 Specifications are subject to change without notice.
 *Note: Fire-Rated doors will be constructed per label service listing and may deviate from above.

