

Rustic| Embossed Hardboard | Structural Composite Lumber Doors | 20 min & Non-Rated
Neutral Pressure, Positive Pressure, Environmental

Standard Models (Bonded): SCL
 Environmental Models (Bonded): SCL-NAUF, SCL-FSC, SCL-NAUF FSC

Product Features and Specifications Interior use only

Thickness	1-3/8", 1-3/4"
Maximum Size	4/0 X 8/0
Minimum Size	1-5 1/2" x 5-11"
Surface Material	Rustic Hardboard
Fire-Rating	20 Minute (Approvals vary by door construction)
Construction	Bonded
Crossbands	Engineered Composite
Vertical Edges*	Mill Option-Fir/Aspen (Additional stile options available upon request)
Horizontal Edges	Wood
Face & Core Assembly Adhesive	Type 1
Core	Structural Composite Lumber (SCL).
Lite Openings	•Wood •Metal Vision Frame
Louvers	Non-rated Only: •Wood •Metal
Factory Finish	•Primed •Standard Color •Custom Color
Warranty	Limited Lifetime. No exterior warranty.
Environmental Options & LEED Credit Contribution (Not all credits may be available with some constructions)	•MR 4-Recycled Content- all models •MR 7-Certified Wood-upon request (Contact Sales) •IEQ 4.4-Low-Emitting Materials- all NAUF models No Added Urea Formaldehyde Resins •CARB Phase II Compliant
Quality Standards (Quality Assurance/ Industry Standards)	Aesthetic: WDMA I.S.1A Architectural Wood Flush Doors (Custom Grade Only)

Note: Mohawk Flush Doors® are manufactured per the standards listed on this page.
 Specifications are subject to change without notice.
 *Note: Fire-Rated doors will be constructed per label service listing and may deviate from above.