

**Veneer Surface | Agrifiber Core Doors | 20 min & Non-Rated**
*Neutral Pressure, Positive Pressure, Environmental*

Standard Models (Bonded): AG FIBER

Environmental Models: AG FIBER-NAUF, AG FIBER-FSC, AG FIBER-NAUF-FSC

**Product Features and Specifications Interior use only**
**Thickness** 1-3/4"

**Maximum Size** 4/0 X 9/0

**Minimum Size** 1-5 1/2" x 5-11'

**Surface Material** Wood Veneer

**Fire Rating** 20 Minute (Approvals vary by door construction)

**Construction** Bonded

**Crossbands** Engineered Composite

**Vertical Edges** Fir (Additional stile options available upon request-Contact Sales)

**Horizontal Edges** Wood

**Face & Core Assembly Adhesive** Type 1

**Core** Agrifiber

**Lite Openings**

- Wood
- Metal Vision Frame

**Louvers** Non-rated Only:  
Wood  
Metal

**Factory Finish Options** •Clear, Standard Stain, Custom Color. Meets WDMA TR-8 and AWS System 9.

**Warranty** Limited Lifetime. No exterior warranty

**Environmental Options & LEED Credit Contribution**  
**(Not all credits may be available with some constructions)**

- MR 4-Recycled Content- all models
- MR 6- Rapidly Renewable Materials - all models
- MR 7-Certified Wood-upon request (Contact Sales)
- IEQ 4.4-Low-Emitting Materials- all NAUF models
- No Added Urea Formaldehyde Resins
- CARB Phase II Compliant

**Quality Standards (Quality Assurance/ Industry Standards)** Aesthetic: WDMA I.S.1A Architectural Wood Flush Doors (Custom Grade Only)

Note: Mohawk Flush Doors® are manufactured per the standards listed on this page.

Specifications are subject to change without notice.

\*Note: Fire-Rated doors will be constructed per label service listing and may deviate from above.