

**Bi-Folds | Veneer Surfaces | Standard Hollow Core Doors**
*Non-Rated*

Standard Models STD HC

Environmental Models: STD HC-NAUF

**Product Features and Specifications Interior use only**
**Thickness** 1-3/4", 1-3/8"

**Maximum Size** 8/0 x 8/0 units

**Surface Material** Veneer

**Crossbands** One Piece High Density Fiberboard (HDF)

**Vertical Edges** Manufacturer's standard:  
Mill Option Softwood-Veneered edge available upon request

**Horizontal Edges** Mill Option Softwood or SCL

**Face & Core Assembly Adhesive** Type 1

**Core** Kraft Paper (5"-7" cell size)

**Factory Finish Options** •Clear, Standard Stain, Custom Color. Meets WDMA TR-8 and AWS System 9.

**Warranty** 1 Year-Interior Use Only

**Environmental Options & LEED Credit Contribution**  
 (Not all credits may be available with some constructions)
 

- Recycled Content- all models
- Low-Emitting Materials- all NAUF models
- CARB Phase II Compliant

**Quality Standards (Quality Assurance/ Industry Standards)** Aesthetic: WDMA I.S.1A Architectural Wood Flush Doors (Custom Grade Only)

**Bifold Hardware** Factory supplied track & hardware:  
L.E. Johnson J100 or L.E. Johnson 1825 (based on weight of unit)  
Surface applied hinges installed by Mohawk

Note: Mohawk Doors® are manufactured per the standards listed on this page.

Specifications are subject to change without notice.

\*Note: Fire-Rated doors will be constructed per label service listing and may deviate from above.