

Veneer Surface | Fire-Resistant Composite Core Doors | 45-90 min
Neutral Pressure, Positive Pressure, Environmental

Standard Models: MINERAL

Environmental Models: MINERAL_NAUF

Product Features and Specifications Interior use only
Thickness 1-3/4"

Maximum Size

	ITS-WH and UL		
	NP	Cat. A (PP)	Cat. B (PPFM)
Single	4/0x10/0	4/0x10/0	4/0x10/0
Pair	8/0x8/0	8/0x9/0	8/0x9/0
DE Pair	8/0x8/0 (45 min only)	8/0x8/0	8/0x8/0

Minimum Size 1/0 x 4/0

Surface Material Wood Veneers

Crossbands One Piece High Density Fiberboard (HDF)

Vertical Edges Manufacturer's standard construction per label service listing with edge band to match face.

Horizontal Edges Manufacturer's standard construction per label service listing.

Face & Core Assembly Adhesive Type 1

Core Fire-resistant composite per label service listing.

Lite Openings Veneer clad or metal lite kits available.

Louvers Fusible link metal

Warranty Lifetime. No exterior warranty

Factory Finish •Clear, Standard Stain, Custom Color. Meets WDMA TR-8 and AWS System 9.

Security Ratings Mineral Core- class 30 per UBC standard 41-1 and ASTM F-476 Section 18
 Particleboard Core- Class 40 per UBC standard 41-1 and ASTM F - 476 Section 18

Acoustic Ratings 21-30 Operable with recommended seals - Must be specified.

Environmental Options & LEED Credit Contribution (Not all credits may be available with some constructions)

- Recycled Content- all models
- Rapidly Renewable Materials- all models with Bamboo veneer
- Certified Wood-upon request
- Low-Emitting Materials- all NAUF models
 No Added Urea Formaldehyde Resins
- CARB Phase II Compliant

Quality Standards (Quality Assurance/ Industry Standards)

Aesthetic: WDMA I.S.1A Architectural Wood Flush Doors (Standard construction)
 *Other association aesthetic standards upon request
 WDMA Performance Duty Level
 *Mineral Core without Blocking - Below Standard
 *Mineral Core with Blocking - Extra Heavy Duty
 (Blocking for mineral core doors provided upon request)

Note: Mohawk doors are manufactured per the standards listed on this page.
 Specifications are subject to change without notice.

*Note: Fire-Rated doors will be constructed per label service listing and may deviate from above.