

Veneer Surface | Particleboard Core Doors | 20 min & Non-Rated
Neutral Pressure, Positive Pressure, Environmental

Standard Models (Non-Bonded): PCFPC

Standard Models (Bonded): PC

Environmental Models: PC-NAUF, PC-FSC, PC-NAUF-FSC

Product Features and Specifications Interior use only
Thickness 1-3/4", 1-3/8"

Maximum Size 4/0 X 10/0 (Limitations apply-based on door construction)

Minimum Size 1-5 1/2" x 5-11' (PC Models) & 0/8' x 1/10' (PCFPC Models)

Surface Material Wood Veneer

Fire Rating 20 Minute (Approvals vary by door construction)

Construction Loose Lay-up (Bonded construction upon request)

Crossbands Engineered Composite

Vertical Edges Fir (Additional stile options available upon request-Contact Sales)

Horizontal Edges Wood

Face & Core Assembly Adhesive Type 1

Core Wood based Particleboard (complies with ANSI A208.1)

Lite Openings

- Wood
- Metal Vision Frame

Louvers Non-rated Only:
Wood
Metal

Factory Finish Options •Clear, Standard Stain, Custom Color. Meets WDMA TR-8 and AWS System 9.

Warranty Limited Limited. No exterior warranty

Environmental Options & LEED Credit Contribution
(Not all credits may be available with some constructions)

- MR 4-Recycled Content- all models
- MR 6-Renewable Materials - all models with Bamboo veneer
- MR 7-Certified Wood-upon request (Contact Sales)
- IEQ 4.4-Low-Emitting Materials- all NAUF models
- No Added Urea Formaldehyde Resins
- CARB Phase II Compliant

Quality Standards (Quality Assurance/ Industry Standards) Aesthetic: WDMA I.S.1A Architectural Wood Flush Doors (Custom Grade Only)

Note: Mohawk Doors® are manufactured per the standards listed on this page.

Specifications are subject to change without notice.

*Note: Fire-Rated doors will be constructed per label service listing and may deviate from above.