

**Veneer Surface | Hollow Core Doors | Non-Rated**  
*Environmental*

Standard Models STD HC  
 Environmental Models: STD HC-NAUF

**Product Features and Specifications Interior use only**

**Thickness** 1-3/4", 1-3/8"

**Maximum Size** 4 x 8 Singles 8 x 8 Pairs

**Minimum Size** 0-8" Minimum width 1-10' Minimum length

**Surface Material** Wood Veneer

**Crossbands** High Density Fiberboard

**Vertical Edges** Mill Option Softwood-Veneered edge available upon request

**Horizontal Edges** Mill Option Softwood

**Face & Core Assembly Adhesive** Type 1

**Core** Kraft Paper \*Lock blocks: (Two) Mill Option Lumber or SCL

**Lite Openings** Wood  
 Metal Vision Frame

**Louvers** Wood

**Factory Finish Options** •Clear, Standard Stain, Custom Color. Meets WDMA TR-8 and AWS System 9.

**Warranty** 1 Year-Interior Use Only

**Security Ratings** N/A

**Acoustic Ratings** N/A

**Environmental Options & LEED Credit Contribution**  
 (Not all credits may be available with some constructions)

- Recycled Content- all models
- Certified Wood-upon request (Contact Sales)
- Low-Emitting Materials- all NAUF models
- No Added Urea Formaldehyde Resins
- CARB Phase II Compliant

**Quality Standards (Quality Assurance/ Industry Standards)** Aesthetic: WDMA I.S.1A Architectural Wood Flush Doors (Custom Grade Only)  
 Other association aesthetic standards upon request

Note: Mohawk Doors® are manufactured per the standards listed on this page.  
 Specifications are subject to change without notice.  
 \*Note: Fire-Rated doors will be constructed per label service listing and may deviate from above.